



LEICA X2

Technical data.



Product	Leica X2	black anodized	silver anodized
Order no.		18 450	18 452
Lens	Leica Elmarit 24 mm f/2.8 ASPH.: 8 elements in 6 groups, 1 aspheric element.		
Focal length	24 mm (35 mm film equivalent).		
Apertures	2.8 to 16 (1/3-EV increments).		
Focusing range	30 cm – ∞.		
AF focusing	1 point, 11 points, spot, face detection.		
Image sensor	16.5 MP, APS-C, CMOS image sensor (effective 16.2 MP).		
Resolution	JPEG in 3:2 format: 4928 x 3264 pixels (16.1 MP), 4288 x 2856 pixels (12.2 MP), 3264 x 2160 pixels (7.1 MP), 2144 x 1424 pixels (3.1 MP), 1632 x 1080 pixels (1.8 MP). DNG in 3:2 format: 4944 x 3272 pixels (16.2 MP).		
Image quality	JPEG super fine, JPEG fine, DNG + JPEG super fine, DNG + JPEG fine.		
Exposure control			
Exposure modes	Automatic program (P), automatic aperture priority (A), automatic shutter priority (S), manual setting (M).		
Exposure compensation	Gradation: 1/3 EV increments, range: ±3 EV.		
Automatic exposure bracketing	1/3 to 3 EV increments, 3 exposures.		
Metering modes	Smart multizone metering, center-weighted metering, selective (spot) metering.		
White balance	Auto, daylight, tungsten, fluorescent, cloudy, shade, electronic flash, 2 manual settings, manual color temperature setting with fine tuning.		
Sensitivity	Auto, ISO 100, ISO 200, ISO 400, ISO 800, ISO 1600, ISO 3200, ISO 6400, ISO 12500.		
Shutter speeds	30 s to 1/2000 s.		
Continuous shooting	3 fps or 5 fps, max. 8 consecutive exposures with constant shooting speed in DNG + JPEG fine quality.		
Exposure modes	Standard, dynamic, natural, b/w natural, b/w high contrast.		
Flash			
Modes	Auto, flash exposure correction, red-eye correction, fill-in flash, slow sync, studio, 1st/2nd curtain sync.		
Hot shoe	Compatible with Leica SF 24D, Leica SF 58 flash units.		
Monitor	2.7"-TFT LCD with 230,000 pixels, wide-angle field of view: 100%.		
Playback modes	16 thumbnails, single frame, magnify (16 x max.), image rotation, deletion protection.		
Storage media	Internal memory: approx. 110 MB. Memory cards: SD, SDHC, SDXC.		
Interfaces	HDMI out, USB (USB 2.0 high-speed).		
Battery (lithium-ion)	Capacity: approx. 450 exposures.		
Dimensions (L x H x D)	Approx. 124 x 69 x 51.5 mm (4.88 x 2.72 x 2.03 in).		
Weight	Approx. 316 g/345 g (11.15 oz/12.17 oz) without/with battery.		
Package includes	Battery (Leica BP-DC8), battery charger (Leica BC-DC8), battery case, leather carrying strap, USB cable, lens cap, user manual.		
Software	Adobe® Photoshop® Lightroom® (free download option after camera registration).		