

Creative freedom for unforgettable images

Product Information





Shown life-size

Creative freedom for unforgettable images With the LEICA D-LUX 3 every picture tells a story : the unique manual setting options offer you freedom to create images that express your own style. Use the high- quality Leica lens to take stunning shots from wide angle to the telephoto range. With O.I.S.optical image stabilization technology and processing at lightning speed, the LEICA D-LUX 3 is setting new standards in its class. Choose between 3 picture formats, achieve first-class image quality thanks to the camera's sensor with a resolution of 10 million pixels and assess your shots on the wide-screen display. Small yet elegant, the LEICA D-LUX 3 is always ready to make your personal view of the world into reality.

_____ The high-aperture LEICA DC VARIO-ELMARIT 6.3-25.2 mm f/2.8-4.9 ASPH. guarantees pictures in Leica quality from 28 mm wide angle to telephoto range. In conjunction with the fast **image signal processor** the D-Lux 3 can achieve such high picture quality thanks to low visual noise and fast processing.

_____ The image stabilizer (O.I.S.) always delivers sharply focused images even with quick snapshots, at twilight or in the zoom range.

<u>Manual setting options</u> give you full freedom when creating your own pictures. But **motif programs and automatic functions** for every application also provide you with optimum picture results quickly and easily. Alone **16 scene modes** are selectable. The 16:9 picture format with full resolution of over 10 MP results in stunning shots and provides for reproduction on HDTV equipment. The 4:3 und 3:2 formats are selectable.

_____ The brilliant **2.8" display** also has the aspect ratio 16:9 for frame-filling presentation of acquired data.

_____ This camera is the latest classic from Leica. Clean minimalist design.

Technical Data

Image type/format	1:1.65" CCD sensor with 10.4 million total pixels and 10 million effective pixels (with an aspect ratio 16:9).
Resolution	In 16:9 format a choice between 4224 x 2376 pixels, 3840 x 2160 pixels, 3072 x 1728 pixels or 1920 x 1080 pixels (corresponds to HDTV
	standard), in Leica 3:2 format a choice between 3568 x 2376 pixels, 3248 x 2160 pixels, 2560 x 1712 pixels or 2048 x 1360 pixels, in 4:3 format
	a choice between 3168 x 2376 pixels, 2880 x 2160 pixels, 2304 x 1728 pixels, 2048 x 1536 pixels, 1600 x 1200 pixels or 1280 x 960 pixels.
Data recording	File formats Still : RAW, JPEG (Fine/Standard), Movie : QuickTime Motion JPEG.
Storage media	SD memory card and multimedia card (64 MB SD card included in scope of supply).
Film speed setting	Choice between automatic or manual ISO 80, ISO 100, ISO 200, ISO 400, ISO 800 or ISO 1600.
Lens	LEICA DC VARIO-ELMARIT 6.3–25.2 mm f/2.8–4.9 ASPH. (equivalent to 28 to 112 millimeters for 35 mm format), 4x optical zoom,
	focal length adjustment via zoom rocker.
Aperture	F 2.8-F 8.0 (WW) F 4.9-F 8.0 (tele)
Optical image stabilizer	Two operating modes : either only for picture-taking or for both monitor and picturetaking.
Distance adjustment range	Choice between normal: 0.5 m (1.6 feet) (with WW)/1.2 m (3.9 feet) (with tele) to infinity,
	or macro: 0.05 m (0.2 feet) (with WW)/0.3 m (1 feet) (with tele) to infinity.
Exposure	Metering Choice between multiple field measurement, emphasis on middle integral measurement, spot measurement, setting can be saved.
	Exposure modes Choice between program automatic, aperture automatic, time automatic and manual setting.
	Exposure compensation ±2 EV in stages, settings from 1/3 EV.
Flash	Flash modes Choice between automatic ON with or without preflash (red-eye reduction), manual ON (fill-in flash) with or without preflash,
	SLOW sync for longer shutter speeds (with preflash), flash OFF. Range wide (sensitivity to Auto): 0.6-4.1 m (2-13.5 feet) (with WW),
	0.3-2.3 m (1-7.5 feet) (with tele). Flash output adjustment ±2 EV in stages, settings from 1/3 EV.
Scene programs	
	candlelight, starry skies, landscapes, print.
	2.8" TFT color display in 16:9 format with 207,000 pixels.
· · · · · · · · · · · · · · · · · · ·	105.7 x 58.3 x 25.6 mm (4.16 x 2.3 x 1.0 inch)
	185 g/220 g (6.5/7.8 oz) (without/with battery, memory card and lens cap)
Accessories	
	Black Order No. 18650, Blue Order No. 18668
	Cognac-brown Order No. 18669
	ACA-DC4 with power cord
	(as spare) LEICA BP-DC4
	Order No. 14100
	For short-range stand Order No. 14110
	Order No. 14320
Digital Adapter	Digitaladapter 2 for LEICA TELEVID Order No.42 303

Trademarks of Leica Camera Group / "Leica" as well as product names = @ Registered trademark / @ 2006 Leica Camera AG / Subject to modifications in design, specification and offer / Product photographs: Alexander Göhr / Photostory: Gaël Turine / Brochure Order No. : German 92100 / English 92101 / French 92102 / Italian 92103 / Spanish 92104 / Hungarian 92105 / 09/06 / AVX / B

Leica Camera AG / Oskar-Barnack-Straße 11 / D-35606 Solms / Telephone +49(0)6442-208-0 / Telefax +49(0)6442-208-333 / www.leica-camera.com